

**Application No.:10/613,299**  
**Response to Requirement of**  
**Restriction**

**Page 3 of 7**

**Amendments to the Claims:**

A clean version of the entire set of pending claims (including amendments to the claims, if any) is submitted herewith per 37 CFR 1.121(c) (3). This listing of claims will replace all prior versions, and listings, of claims in the application.

**Listing of Claims:**

1. (Original) An optical testing unit for measuring sensitivity of an optical device under test (DUT) over an operating range of the DUT comprising:

an optical transmitter, which transmits an optical test signal that is transmitted to the DUT;

an optical receiver, which receives an input signal from the DUT;

a graphical user interface, which provides an interface with a user; a memory module, said memory module comprising a sensitivity module; and

a controller, selectively coupled to said transmitter, said receiver and said graphical user interface, wherein said controller provides a central control of said transmitter, said receiver and said graphical user interface.

2. (Original) An optical testing unit as recited in claim 1, wherein said memory further comprises a calibration module, said calibration module comprising information utilized by said controller during a calibration procedure.

3. (Original) An optical testing unit as recited in claim 1, wherein said memory module further comprises a standard success criteria module, said standard

**Application No.:10/613,299**  
**Response to Requirement of**  
**Restriction**

**Page 4 of 7**

success criteria module comprising information utilized by said controller to compare test results to an industry standard.

4. (Original) An optical testing unit as recited in claim 1, wherein the unit is disposed in a housing.

5. (Original) An optical test unit as recited in claim 1, further comprising an optical power monitor, which is controlled by said control unit.

6. (Original) An optical testing unit as recited in claim 5, further comprising an optical attenuator, which receives said optical test signal and selectively attenuates said test signal prior to providing an attenuated input signal to the DUT.

7. (Original) An optical test unit as recited in claim 6, wherein said control unit actively adjusts at least one of: an output power level of said transmitter; and an attenuation level of said attenuator to transmit said test signal at a desired power level as measured by said optical power monitor.

8. (Original) An optical test unit as recited in claim 7, wherein said control unit iteratively performs said adjustments.

9. (Original) A method of measuring sensitivity of an optical component, the method comprising:

providing an optical testing unit disposed in a housing;

providing a test optical signal as an output signal from said optical testing unit

**Application No.10/613,299**  
**Response to Requirement of**  
**Restriction**

**Page 5 of 7**

to a device under test (DUT);  
receiving an input signal from said DUT at said optical testing unit;  
measuring said sensitivity from said input signal; and  
providing a control unit within said housing which controls various components  
in said optical test unit.

10. (Original) A method as recited in claim 9, wherein said test optical signal is  
from an optical transmitter within said optical testing unit.

11. (Original) A method as recited in claim 9, wherein said input signal is  
received at an optical receiver within said optical testing unit.

12. (Original) A method as recited in claim 9, wherein said controller further  
comprises a memory module.

13. (Original) A method as recited in claim 12, wherein said memory module  
further comprises a sensitivity module.

14. (Original) A method as recited in claim 13, wherein said memory module  
further comprises a test module.

15. (Original) A method as recited in claim 13, wherein said memory module  
further comprises a calibration module.

16. (Original) A method as recited in claim 13, wherein said memory module  
further comprises a standard success criteria module.

17. (Original) A method as recited in claim 9, wherein said optical testing unit